

WORLD INTELLECTUAL PROPERTY ORGANIZATION  
International Bureau

(51) International Patent Classification <sup>6</sup> : H04M 3/50		A2	(43) International Publication Date: 1 May 1997 (01.05.97)	WO 97/16014
(21) International Application Number: PCT/US96/16919		(81) Designated States: JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).  Published <i>Without international search report and to be republished upon receipt of that report.</i>		
(22) International Filing Date: 22 October 1996 (22.10.96)				
(30) Priority Data: 08/548,178      25 October 1995 (25.10.95)      US				
(71) Applicant: GENESYS TELECOMMUNICATIONS LABORATORIES, INC. [US/US]; 11th floor, 1155 Market Street, San Francisco, CA 94103 (US).				
(72) Inventors: MILOSLAVSKY, Alec; 10 Whitman Court, San Carlos, CA 94070 (US). GOECKE, Jason; 490 Lombard Street #16, San Francisco, CA 94133 (US).				
(74) Agent: CHAN, Hark, C.; Wilson, Sonsini, Goodrich & Rosati, 650 Page Mill Road, Palo Alto, CA 94304-1050 (US).				

Figure 1 is a block diagram of a video conferencing system. The system includes a PSTN (104) connected to two Video Kiosks/Calling parties (102 and 103) via lines 106 and 108. A central PBX or PSTN Switch (112) is connected to the PSTN via line 107 and to the Video Kiosks via line 144. The PBX switch is also connected to a CTI Link (132), which in turn connects to a CTI/PBX Server (113). The CTI/PBX Server is connected to a Mail Server (124), a Routing Server/Video ACD (114), and a Database (120). The Database is connected to the Mail Server, the Routing Server/Video ACD, and the CTI/PBX Server. The Mail Server is connected to three Video Stations (115, 116, 117) via lines 122. The Routing Server/Video ACD is connected to the Video Stations via lines 140 and 148. The Video Stations are connected to a Communications Network (121) via lines 122. The Communications Network is connected to the Mail Server, the Routing Server/Video ACD, and the Database via lines 140 and 148. The entire system is labeled 100.

**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic			SE	Sweden
CG	Congo	KR	Republic of Korea	SG	Singapore
CH	Switzerland	KZ	Kazakhstan	SI	Slovenia
CI	Côte d'Ivoire	LI	Liechtenstein	SK	Slovakia
CM	Cameroon	LK	Sri Lanka	SN	Senegal
CN	China	LR	Liberia	SZ	Swaziland
CS	Czechoslovakia	LT	Lithuania	TD	Chad
CZ	Czech Republic	LU	Luxembourg	TG	Togo
DE	Germany	LV	Latvia	TJ	Tajikistan
DK	Denmark	MC	Monaco	TT	Trinidad and Tobago
EE	Estonia	MD	Republic of Moldova	UA	Ukraine
ES	Spain	MG	Madagascar	UG	Uganda
FI	Finland	ML	Mali	US	United States of America
FR	France	MN	Mongolia	UZ	Uzbekistan
GA	Gabon	MR	Mauritania	VN	Viet Nam

## VIDEO TELECOMMUNICATION ROUTING SYSTEMS AND METHODS

### Background of the Invention

Telephone is one of the most widely used communication equipments in the world. At first, it was merely a convenient tool to allow people to communicate while they are physically separated. Recently, many companies use telephones to market products and services, provide technical supports to consumer products, allow customers to access their own financial data, etc. Thus, telephone is becoming a major business and marketing tool.

In order to more effectively use telephone for business and marketing purposes, call centers have been developed. In a call center, a large number of agents handle telephone communication with customers. The matching of calls between customers and agents is typically performed by software. A simple example is used here to describe a few of the many advantages of using call centers. When a call is made to a call center, the telephone number of the calling line is typically made available to the call center by a telephone carrier. Based on this telephone number, the software in the call center can access a database server to obtain information about the customer who has been assigned that phone number. The software can

now route the call to an agent who can best handle the call based on predefined criteria (e.g., language skill, knowledge of products the customer bought, etc.). The software immediately transfers relevant information to a computer screen used by the agent. Thus, the agent can gain valuable information about the customer prior to receiving the call. As a result, the agent can more effectively handle the telephone transaction.

It can be seen from the above example that the enabling technology requires a combination of telephone switching and computer information processing technologies. The term commonly used for this combined technology is computer-telephony-integration (CTI).

Recent advances in computer technology and compression methods allow video signals to be digitized and compressed in real time using inexpensive chips. Because compressed digital video data contains only a relatively small number of bits per frame, the data can be sent from one place to another using a relatively low bandwidth communication channel. For example, it is found that acceptable video telecommunication can be achieved if a communication channel has a bandwidth of about 128 kilobits per second (Kbps). This bandwidth can be provided by a standard integrated services digital networks (ISDN) line. It is anticipated that the costs of ISDN lines (or telecommunication channels having similar bandwidth) will decrease drastically. As a result, it is predicted that video telecommunication systems will be widely used in the near future.

Current video communication systems do not allow for a call to be passed off or transferred to one of a plurality of video systems therein. Attempting such operation will destroy the call and disconnect the caller from the call center. As a

result of this limitation, conventional video telecommunication systems cannot utilize the resources and advantages of a call center.

5 In view of the proven commercial values of the CTI technology and call center operation, it is desirable to integrate video telecommunication with existing CTI technology and call center operation.

### **Summary of the Invention**

10 The present invention involves a system for routing video telecommunication calls received by a central exchange to one of a plurality of video stations connected to the exchange. In order to deliver acceptable video performance, each video communication channel occupies at least two voice-quality telephone channels. One aspect of the present invention is a method and device for connecting these two  
15 telephone channels to the same video station served by the central exchange.

The routing system of the present invention comprises a telephone switch for connecting a first one of the at least two incoming telephone channels to a video station. The system then identifies a second incoming telephone channel as one of  
20 the two telephone channels for carrying the video communication. The switch then connects the second telephone channel to the same video station.

In one embodiment of the present invention, an Inwats (inward wide area telecommunication service, or toll-free 800) telephone number is assigned for video  
25 telecommunication. The telephone numbers of the calling video device is also preassigned. The calling video device can initiate a video telecommunication call by dialing the Inwats telephone number two times. The public switched telephone

network delivers telephone identification information of the dialing device (i.e., the automatic number identification, or ANI, of the two low bandwidth telephone channels) and the Inwats number to the routing system.

5           Upon receiving the call, the routing system recognizes the call as a video call because the toll-free 800 number is assigned for video telecommunication. The routing system also receives the ANI of the calling video device. The routing system then searches a database for a suitable video station to connect the call. Because the telephone numbers associated with the calling video device are preassigned, the  
10          routing system is able to anticipate the second ANI of the channel which carries the video telecommunication. Upon receiving a call having the second ANI, the routing system then connects this call to the same video station.

15           These and other features of the present invention will become apparent from the following description when read in conjunction with the drawings and the appended claims.

### **Brief Description of the Drawings**

20           Fig. 1 is a block diagram of a video routing system of the present invention.

            Fig. 2 is a flow chart of a trunk route script which allows a host of the present invention to control the operation of a private branch exchange.

25           Fig. 3 is a flow chart showing the operation of the video routing system of the present invention.

Fig. 4 is a drawing showing the logical connection between components in a call station of the present invention.

### **Detailed Description of the Invention**

5

The present invention comprises a novel video telecommunication routing system and related methods. The following description is presented to enable any person skilled in the art to make and use the invention. Description of specific applications is provided only as examples. Various modifications to the preferred  
10 embodiments will be readily apparent to those skilled in the art, and the general principles defined herein may be applied to other embodiments and applications without departing from the spirit and scope of the invention. Thus, the present invention is not intended to be limited to the embodiments shown, but is to be accorded the widest scope consistent with the principles and features disclosed  
15 herein.

Fig. 1 is a block diagram of a video routing system 100 of the present invention. System 100 comprises a video kiosk 102 which originates a video call and a call center 110 which accepts and assigns an appropriate video agent to process the  
20 call. Video Kiosk 102 and call center 110 are connected to a public-switched telephone network (PSTN) 104 via telephone lines 106 and 107, respectively. As will be explained below, line 106 is preferably a basic rate interface and line 107 is preferably a primary rate interface. Consequently, video calls between video kiosk 102 and call center 110 are carried by PSTN 104.

25

Call center 110 comprises a video routing device 111 which accepts calls (including video calls) when predetermined phone numbers are dialed, and then

routes individual call to one of a plurality of stations in accordance with predefined criteria. These stations include video stations 115-117. In an embodiment of the present invention, the criteria could vary in real time as the characteristics of the calls and video stations change.

5

It is possible for call center 110 to process video calls from other video kiosks, such as kiosk 103. Call center 110 may also process conventional voice calls.

10 In one embodiment of the present invention, video stations 115-117 can be connected to a communication network 121. This network could be a local area network commonly used in many offices. Other devices, such as a database server 122, can also be connected to network 121. Information of video stations, call center personnel and customers can be stored in database server 120. This information is accessible by video stations 115-117. It should be appreciated that database server  
15 120 does not have to be a sophisticated database management system. It could be as simple as a table stored in a small data processing device. Video routing device 111 may optionally be connected to database server 120 so as to access the information. This information can also be stored inside video routing device 111.

20 An example of the types of video telecommunication that can be advantageously handled by routing system 100 is intelligent routing of a video conference between a customer located at video kiosk 102 and an appropriate agent sitting by one of the video stations in call center 110.

25 Video routing device 111 comprises a switching device 112 for accepting calls from PSTN 104. Switching device 112 could be a automatic call distributor (ACD)/private branch exchange (PBX) or a PSTN switch. It should be appreciated



that switching device 112 (hereinafter "ACD/PBX 112") can be a customer premise equipment or may be provided by a telephone communication carrier. ACD/PBX 112 contains a high bandwidth port 144 (for connecting to PSTN 104) and a plurality of low bandwidth ports (such as ports 146-150). Some of these ports can be connected to video stations 115-117. The other low bandwidth ports can be connected to voice-based devices. Each of the low bandwidth ports is assigned one or more directory numbers. In one embodiment of the present invention, two directory numbers (corresponding to two telephone channels) are assigned to a video station.

ACD/PBX 112 is also connected to a CTL/PBX server 113 through a computer-telephony-integration (CTI) link 123. Video routing device 111 comprises two other servers: a routing server/video ACD 114 for routing video calls and a stat-server 124 for storing historic information of call center 110. CTL/PBX server 113 functions as an interface between these two servers and ACD/PBX 112. These three servers are connected to communication network 121. In the present embodiment, the function of these servers are provided by software modules. As explained below, these three servers can be used in combination with a conventional ACD/PBX to achieve the video routing function of the present invention

High bandwidth port 144 of ACD/PBX 112 is preferably connected to a high capacity telephone line, such as a primary rate interface (PRI) as defined in the CCITT ISDN 1.431 standard. This is one of the standards of the international ISDN protocol. Low bandwidth ports 146-145 could be a single voice channel or a basic rate interface (BRI) as defined in CCITT ISDN 1.430 standard. Basically, BRI offers two 56 kilo-bit-per-second (Kbps) user data channels (the "bearer" or B channels) and one 16 Kbps signaling channel (the D channel). This interface is also referred to

as 2B+D. The combined bandwidth is 128 Kbps. The PRI offers twenty three user data channels and one 64 Kbps signaling channel. This interface is also referred to as 23B+D

5 In order to deliver video information at an acceptable level of quality (e.g., 15 frame per second), current compression technology prefers a bandwidth of at least 112 to 128 Kbps. This amount of bandwidth cannot be provided by a single telephone channel but could be provided by an ISDN BRI. Thus, in Fig. 1, line 106 connecting video kiosk 102 to PSTN 104 is preferably a BRI line.

10 As discussed above, a BRI line essentially comprises two telephone channels. These two telephone channels must be connected to the same low bandwidth port of PBX 142 in order to allow all the video data from video kiosk 102 to be transmitted to the same video station. A conventional PBX does not have the ability to recognize  
15 that two telephone channels originated from the same video kiosk. Thus, it is not possible for it to connect them to the same video station.

In one embodiment of the present invention, the servers in video routing device 111 (i.e., CTI/PBX server 113, stat-server 124 and routing server/video ACD  
20 114; these three servers are collectively called the "host") are used in combination with a conventional PBX to route calls originated from video kiosk 102 to the appropriate low bandwidth port. In this embodiment, ACD/PBX 112 is a conventional PBX which comprises a data processing device capable of executing an internal trunk route script. This script contains a plurality of commands which  
25 control the operation of ACD/PBX 112. For example, the script can connect calls received at high bandwidth port 144 to low bandwidth ports in accordance with certain criteria, determine the type of music or announcement to play when a call is

put on hold, select the strategy to queue calls when all low bandwidth ports are busy, etc.

In this embodiment of the present invention, the above described servers are used to determine the operation of ACD/PBX 112 (i.e., the internal trunk route script is essentially disabled). As a result, intelligence and routing decisions are moved from ACD/PBX 112 to the host. Fig. 2 is a flow chart 200 showing a trunk route script which allows the host to control the operation of ACD/PBX 112. ACD/PBX 112 receives an incoming call (step 202). ACD/PBX 112 places a request to the host for routing the call (step 204). ACD/PBX 112 then waits for a response from the host (step 206). If it receives a response from the host, control is transferred to host, which then performs routing operation in accordance with criteria determined by the host (step 208). Flow chart 200 then ends, and another call can be processed by ACD/PBX 112 and the host. If ACD/PBX 112 does not receive a response from the host, it determines whether a response timeout (e.g., 10 seconds) has elapsed (step 210). If the answer is yes, ACD/PBX 112 then executes its internal script (step 212). Thus, the internal script provides a default routing routine for the call center. Flow chart 200 then ends, and another call can be processed by ACD/PBX 112 and the host. If the answer is no, ACD/PBX 112 continues to wait (i.e., flow chart 200 branches back to step 206).

In the preferred embodiment of the present invention, video routing is performed by combining the resources of stat-server 124, routing server/video ACD 114, and CTI/PBX server 113. Stat-server 124 contains a database for storing all relevant activities of call center 110 (e.g., the current status and history of activities of all low bandwidth ports). Routing server/video ACD 114 routes calls to appropriate low bandwidth ports based on factors such as the information contained

in stat-server 124, the information delivered by ACD/PBX 112 and the status of various low bandwidth ports. CTI/PBX server 113 acts as a bridge between ACD/PBX 112 at one end and stat-server 124 and routing server/video ACD 114 at the other end. CTI/PBX server 113 is designed to interface with PBXs manufactured by different vendors and present a uniform application program interface (API) to stat-server 124 and routing server/video ACD 114. An advantage of this arrangement is that individual components in video routing device 111 could be replaced and enhanced separately. For example, substantially the same routing server/video ACD and stat-server could be used with PBXs from different manufacturers by changing CTI/PBX server 113.

The operation of an embodiment of video routing system 100 is now described in connection with flow chart 250 of Fig. 3. The video routing system in this embodiment operates in a telephone system in which two separate telephone numbers are associated with an ISDN channel. It should be noted that this embodiment can be modified in a manner described below to function in a telephone system in which only one telephone number is associated with an ISDN channel.

In system 100, a regular toll-free 800-number is pre-assigned to carry video information. Thus, video kiosk 102 dials this number twice, each time using a different phone number associated with the ISDN channel (step 252). The time gap for connecting these two calls to call center 110 by PSTN 104 ranges from less than a second to several seconds. Typically, the gap is below one minute.

PSTN 104 connects the calls to call center 110 (step 254). Each time when the 800-number is dialed, PSTN 104 delivers two pieces of information to ACD/PBX 112: a "dial number identification system" (DNIS) for uniquely identifying the toll-

free 800-number and an "automatic number identification" (ANI) for uniquely identifying the telephone line which originates the call. In this embodiment, the above described toll free 800-number and the ISDN line connected to video kiosk 102 are pre-assigned for video conference purposes. The DNIS and ANIs of the corresponding 800-number and ISDN line should have been previously stored in a database (which could be located in routing server/video ACD 114 or database server 120).

In the present invention, ACD/PBX 112 transfers control of calls to the host (step 258). When ACD/PBX 112 receives the DNIS and the first of two ANIs from PSTN 104, it sends these two numbers to CTI/PBX server 113, which in turn sends them to routing server/video ACD 114. Routing decision is not made by ACD/PBX 112. Because this DNIS is one of the numbers recognized by routing server/video ACD 114 to be associated with a video call, the video routine algorithm of routing server/video ACD 114 is invoked. This serves as a convenient method for screening out non-video calls.

Routing server/video ACD 114 then determines if this is a new video call or a part of an existing video call (step 260). It branches to a "DN-Relate" database. An example of a DN-Relate database is shown in Table 1:

**Table 1: DN-Relate**

DN1#	DN2#	Status	Time Stamp	Related ANI
1000	1001	Available	9:20	
1040	1041	Unavailable	10:10	
1060	1061	Waiting	10:32	1213

It should be appreciated that the format and information contained in table 1 is for illustrative purposes only. The design of the table can be easily changed and enhanced by persons of ordinary skill in the art.

5 In table 1, the entries under the columns "DN1#" and "DN2#" correspond to the pairs of directory numbers assigned to video stations. Each pair of directory numbers will be connected to the same video station. The column entitled "status" indicates the status of the directory numbers. If the entry is "unavailable," these directory numbers are not available (e.g., video station not yet logged in) and should  
10 not be connected to a new video call. If the entry is "available," these directory numbers could be used to connect to a new video telecommunication. If the entry is "waiting," one of the two ANIs has been received, and a second ANI needs to be received to complete the video telecommunication. The entries under "time stamp" contain time-related information. This information could be used as part of the input  
15 variables of a routing algorithm, e.g., the video station waited longest for a video call should be connected first. The entries under "Related ANI" contain the second of two ANIs used for completing a video connection. The entries of this column can be used by routing server/video ACD 114 to connect appropriate video calls to the correct video station.

20

The last row in table 1 is now explained. The numbers 1060 and 1061 under DN1# and DN2#, respectively, correspond to the directory numbers assigned to the same video station. The status is "waiting," indicating that one of the directory numbers, e.g., 1060 under DN1#, has previously been connected to an incoming  
25 video call and this video station is waiting for the second incoming video call. The time under time stamp corresponds to the time the first call is received. The number

under "related ANI", i.e., 1213, corresponds to the ANI of the anticipated second call. The method of entering the anticipated ANI in table 1 will be explained below.

Routing server/video ACD 114 compares the ANI obtained from ACD/PBX 112 to the ANIs stored in the DN-Relate database (step 262). If there is a match, routing server/video ACD 114 knows that this video call relates to an existing call. For example, if the received ANI is 1213, the database in table 1 indicates that video routing system 100 is waiting for this ANI to complete a video connection, and this call should be routed to DN# 1061. The status column of the corresponding row should be updated to indicate that video telecommunication has been established (step 264). Routing server/video ACD 114 then connects the video call to the waiting directory number (i.e., the corresponding entry under DN2#) indicated in the database (step 266). Flow chart 250 ends and another call can be processed.

If routing server/video ACD 114 does not find any match, it needs to look for an available video station (step 270). It checks to see if a video station is available (step 272). Assuming that more than one video stations are available, one of them will be selected in accordance with predetermined criteria. For example, the time stamp column of a pair of available directory numbers indicates the time this pair of directory numbers first became available. This information could be used as a factor to select the appropriate video station. After an available video station is selected, routing server/video ACD 114 updates the status of this station (step 280). Specifically, it sets the corresponding status to "waiting" and sets the time stamp in the database. Routing server/video ACD 114 then connects the incoming call to the directory number (under "DN1#") of the selected video station (step 282).

Routing server/video ACD 114 needs to obtain the corresponding ANI for the remaining call (step 286). It jumps to a "ANI-relate" database. This database contains entries of the pairs of phones numbers associated with the ISDN lines assigned for video telecommunication purposes. For example, if a first ISDN line (connected to a first video kiosk) associates with ANIs 1212 and 1213 while a second ISDN line (connected to a second video kiosk) associates with ANIs 3276 and 3277, the ANI-relate database would have entries shown in Table 2:

**Table 2: ANI-Relate**

First ANI	Second ANI
1212	1213
1213	1212
3276	3277
3277	3276
(Other pairs of ANIs)	

It should be appreciated that the format and information contained in table 2 is for illustrative purposes only. The design of the table can be easily changed and enhanced by persons of ordinary skill in the art.

As an example, if the ANI received by routing server/video ACD 114 is 3276, the ANI-Relate database indicates that the ANI associated with the same video call is 3277. Thus, routing server/video ACD 114 is able to obtain the second of a pair of ANIs associated with a video connection. It then returns to DN-Relate database (see table 1) and places the number 3277 under the column "related ANI" of the selected video station. Routing system 100 then waits for incoming calls having this second ANI. Flow chart 250 ends and waits for the next call.



If there is no available video station, routing server/video ACD 114 sends the call to a queue to wait for an available station (step 292). In the present invention, a new method is used to queue video calls. This method is different from those used on standard voice calls. As stated earlier a call cannot be connected to one point and then disconnected to another point. Such operation will destroy the call. As a result, the new method, described below, is needed to handle the queuing.

In step 294, routing server/video ACD 114 checks to see if the video call has been in the queue for longer than an allowed time (i.e., the timeout period). If the allowed time has expired, routing server/video ACD 114 records the ANI that attempts to call the call center (step 296). When a video station is later available, this ANI can be retrieved by a video agent and a call can be placed by that video agent to the kiosk (or person) which had originated the call. In the mean time, ACD/PBX 112 is instructed to disconnect the video call and return a busy signal (step 298). This is the least desirable option. It should be used when no video agents are available and none are seen to become available within a relatively short time frame. The timeout period is set to reflect this consideration.

If the video call has been in the queue for shorter than the allowed time, routing server/video ACD 114 continues to try to connect the call (step 302). That is, flow chart 250 loops back to step 272. During this period of time, the video call remains in a ringing state. The loop continues until the timeout has elapsed. At that time, steps 296 and 298 are executed.

It can be seen from the above description of flow chart 250 that video routing device 111 is able to receive video calls and connect them to appropriate video stations (if available) in call center 110. Video routing device 111 could also access database server 120, if there is a need to do so, to obtain additional information about

video kiosk 102 and the video station selected for connection. This information can be sent to an agent monitoring the selected video station.

As pointed out above, video routing device 111 can also be used for the situation where only one phone number is assigned to an ISDN channel. In this case, there is no need to generate the "ANI-relate" database because the entries in the first and second columns will be the same. The calling ANI is directly written to the appropriate row of the "related ANI" column. This is because the calling ANI and the anticipated second ANI are the same.

Fig. 4 is a drawing showing the logical connection between components in call center 110. It can be seen from Fig. 4 that ACD/PBX 112 is connected only to CTI/PBX 113. Information regarding calls is communicated to stat-server 124 by CTI/PBX 113 so that stat-server 124 can record all telephone transactions. CTI/PBX server 113 is also connected to routing server/video ACD 114 for allowing it to route video calls. Routing server/video ACD 114 is connected to stat-server 124 because the information stored therein is used by routing server/video ACD 114 to route calls. Further, stat-server 124 records routing instructions of routing server/video ACD 114. Routing server/video ACD 114 is also connected to database server 120 to obtain additional information for routing calls. Stat-server 120 and database server 120 are connected so that information contained therein can be shared and updated.

Video stations 115-117 are connected to routing server/video ACD 114 so that video calls can be routed thereto. Video stations 115-117 are also connected to database server 120 so that information regarding customers, products, etc., can be downloaded from database server 120.

It should be appreciated that even though CTI/PBX 113, routing server/video ACD 114, stat-server 124 and database server 120 are shown as separate components, they could be combined into one, two or three components residing on one or more data processing devices.

5

The invention has been described with reference to specific exemplary embodiments thereof. Various modification and changes may be made thereunto without departing from the broad spirit and scope of the invention. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense; the invention is limited only by the provided claims.

10

**WHAT IS CLAIMED IS:**

1. A system for routing video calls received by a centralized exchange to one of a plurality of video stations, said video call occupying at least two telephone  
5 channels and originated from a video device through a PSTN to said centralized station, said system comprising:
  - a telephone switch for connecting a first one of said at least two telephone channels to a video station;
  - means for identifying a second telephone channel as one of said two telephone  
10 channels; and
  - said telephone switch connecting said second telephone channel to said video station.




Figure 1

2/5




Figure 2

3/5




Figure 3A

SUBSTITUTE SHEET (RULE 26)

4/5




Figure 3B

SUBSTITUTE SHEET (RULE 26)



5/5




Figure 4

**THIS PAGE BLANK (USPTO)**




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification <sup>6</sup> : H04M 3/50, H04N 7/14, H04M 11/00	A3	(11) International Publication Number: <b>WO 97/16014</b>
(21) International Application Number: PCT/US96/16919		(43) International Publication Date: 1 May 1997 (01.05.97)
(22) International Filing Date: 22 October 1996 (22.10.96)		(81) Designated States: JP, European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
(30) Priority Data: 08/548,178 25 October 1995 (25.10.95) US		<b>Published</b> <i>With international search report. Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments.</i>
(71) Applicant: GENESYS TELECOMMUNICATIONS LABORATORIES, INC. (US/US); 11th floor, 1155 Market Street, San Francisco, CA 94103 (US).		(88) Date of publication of the international search report: 17 July 1997 (17.07.97)
(72) Inventors: MILOSLAVSKY, Alec; 10 Whitman Court, San Carlos, CA 94070 (US). GOECKE, Jason; 490 Lombard Street #16, San Francisco, CA 94133 (US).		
(74) Agent: CHAN, Hark, C.; Wilson, Sonsini, Goodrich & Rosati, 650 Page Mill Road, Palo Alto, CA 94304-1050 (US).		

## (54) Title: VIDEO TELECOMMUNICATION ROUTING SYSTEMS AND METHODS

## (57) Abstract

The present invention involves a system for routing video telecommunication calls received by a central exchange to one of a plurality of video stations connected to the exchange. Each video communication channel occupies two voice-quality telephone channels. Video telecommunication calls are initiated by a video device having preassigned telephone numbers. The video device then calls the central exchange. The routing system contains a telephone switch that connects the first incoming telephone channel to a video station. The ANI of the calling video device is recorded. When the second incoming telephone channel of the same video station is received, its ANI is detected. Because the telephone numbers associated with the calling video device are preassigned, the routing system is able to anticipate the second ANI of the channel which carries the video telecommunication. Upon receiving a call having the second ANI, the routing system then connects this call to the same video station.



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroun	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

# INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/US 96/16919

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 6 H04M3/50 H04N7/14 H04M11/00

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 6 H04M H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	AT & T TECHNICAL JOURNAL, vol. 70, no. 5, 1 September 1991, pages 36-44, XP000244602 HARVEY D E ET AL: "CALL CENTER SOLUTIONS" see page 40, left-hand column, line 17 - page 41, left-hand column, line 3 see figure 2 ---	1
A	EP 0 376 517 A (AMERICAN TELEPHONE & TELEGRAPH COMPANY) 4 July 1990 see abstract see page 2, line 39 - page 3, line 17 see figures 1,2,9 --- -/-	1

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

### \* Special categories of cited documents:

- "A" document defining the general state of the art which is not considered to be of particular relevance
- "E" earlier document but published on or after the international filing date
- "L" document which may throw doubt on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- "O" document referring to an oral disclosure, use, exhibition or other means
- "P" document published prior to the international filing date but later than the priority date claimed

- "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
- "&" document member of the same patent family

2

Date of the actual completion of the international search  16 May 1997	Date of mailing of the international search report  02.06.97
Name and mailing address of the ISA European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+ 31-70) 340-2040, Tx. 31 651 epo nl, Fax (+ 31-70) 340-3016	Authorized officer  Gijssels, W

Internal Application No  
PCT/US 96/16919

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

# INTERNATIONAL SEARCH REPORT

information on patent family members

International Application No

PCT/US 96/16919

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0376517 A	04-07-90	US 5062103 A CA 2004275 A,C CA 2108381 A,C DE 68926880 D DE 68926880 T ES 2088900 T JP 2265345 A	29-10-91 29-06-90 30-06-90 29-08-96 19-12-96 01-10-96 30-10-90
FR 2671252 A	03-07-92	US 5184345 A DE 4142738 A JP 4304752 A	02-02-93 09-07-92 28-10-92
EP 0528732 A	24-02-93	FR 2680621 A	26-02-93
EP 0532972 A	24-03-93	DE 4131062 C	05-11-92
US 5155761 A	13-10-92	EP 0587950 A	23-03-94

**THIS PAGE BLANK (USPTO)**



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

### **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

### **IMAGES ARE BEST AVAILABLE COPY.**

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

**THIS PAGE BLANK (USPTO)**